

* PRODUCT INFORMATION *

HUSKEY™ TUFF STUFF GREASE

DESCRIPTION

HUSKEY TUFF STUFF is a new generation grease designed for today's demanding industries. It represents the "state of the art" in grease technology, combining the finest base oil stocks, additives and synthetic thickeners available to provide a truly multi-service, friction reducing, non-melting grease with unmatched protection in normal and severe service applications.

HUSKEY TUFF STUFF is a blend of the highest quality paraffinic base oils and polymers coupled with **HUSKEY'S** newest proprietary extreme pressure additive which forms a tough durable film of protection from friction, wear and corrosion over a wider temperature range (-20EF. to 400EF.).

HUSKEY TUFF STUFF'S unique formulation provides superior adhesion to metal surfaces that does not easily wash off, run out or separate even under adverse conditions of water, steam or dilute chemicals thus providing lower grease consumption and extended lubrication cycles.

USAGE

HUSKEY TUFF STUFF provides unmatched performance in a wide variety of conventional and severe service applications found in a diverse range of industrial, marine, mining, construction, agricultural and automotive applications.

HUSKEY TUFF STUFF is recommended for all roller, sleeve and pillow block bearings, bushings, couplings, universal joints, and sliding surfaces where a multi-purpose or extreme pressure grease is required. The use of **HUSKEY TUFF STUFF** can allow you to reduce your grease inventory.

ADVANTAGES

- Withstands Extreme Pressures
- Wide Temperature Range
- Excellent Metal Adherence
- Prevents Rust & Corrosion
- Reduces Friction & Wear
- Will Not Melt or Run Out
- Highly Water Resistant
- Reduces Grease Inventories

TYPICAL SPECIFICATIONS

TEST	ASTM TEST METHOD	RESULTS
N.L.G.I. Grade	-	2
Worked Penetration	D-217	
60 stokes		285
10,000 strokes		300
Base Oil Viscosity	D-445	
SUS @ 100°F		1200
SUS @ 210°F		85
Pour Point, °F	D-97	-20
Flash Point, °F	D-92	410
Dropping Point, °F	D-566	None
Corrosion Preventative Test	D-1743	Pass
Timken OK Load, lbs.	D-2509	70

PACKAGE AVAILABILITY

14 oz. cartridges, 5-gal. Pails, 15-gal. Kegs, 55-gal. Drums

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

1/03



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE